Instructions (DFS-DSS-M003)

Product Introduction:

This product is from D. F. S feathways (M) Ltd independent research and development, than been independent intellectual property risks. It is spen display for the Mobile Phone MPA_MPL and other display stand of the real commodity. It has a good effectively anti-theft for the display product while the customer was touching and experiencing it. So that it letuustomer have stronger buy desire.

Function of the product:

- Main Function of the product
- 1. The customer experience in display.
- 2. Anti-theft for display goods effectively.
 3. Charging for the display goods

Description of Accessories:

1. A set of holder.



 $\begin{tabular}{ll} 2. \ Power \ adapter \\ (According to the requirements of our customers to configuration) \end{tabular}$



3. Several security display stand match one remote controller $\dot{}$



4. One set of instrutions

5.0ne Srew

6. A tie

The structure of the holder



Operation steps:

- (Nost DC hole next to the LED light will turn red, When charging, fully charged the LED turns off)

 2. Slide the systch on the bottom of the power, turn om power.

 3. The remote controller within 15mm to active the holder.

 4. Tear off the MS sticker of the holder bottom.

 5. Put the holder on the clean table. (Need to press at least for 10 minutes)

 6. Conderally the displayed this receiver about holes.

- 6. Goods will be displayed with scress above the host
 7. Tear off the 3M sticker of the small touch side
 8. stick Contactor on the surface of the commodity. (Need to press at least for 10 minutes)

When finished the seven steps, the holder will sound a beep, the LED light will flicker blue light once 5 seconds, the holder will in the work state.

Operation schematic drawing



 $S \ \text{tep 1}: \ \text{Insert the power adapter} \\ \text{to charge for the holder}.$ (End of the power adapter DC kong he other end of the power)



Step2: Slide the switch on the bottom of the power, turn on power.





Step3: The remote controller aim at the signal receiver Parallel, press the remote controller within 15mm to active the holder. Che moment of pressing the romote button, the host will issue a bit of tone)



 $\ensuremath{\mbox{Step 4:Tear}}\xspace$ off the 3M sticker of the holder bottom.



Step5: Put the holder on the clean table. (Need to press at least for 10 minutes)



Step 6: Goods will be displayed with screws above the host





Step 7: Tear off the 3M sticker of the small touch side



Step8:stick Contactor on the surface of the commodity.

Odity. (Need to press at least for 10 minutes)

When finished the seven steps, the holder will sound a beep, the LED light will flicker blue light once 5 seconds, the holder will in the work state.

Notes:

- 1. Keep the controller at a shorter distance with the Signal receiver hole (within 15 mm)
 2. avoid irradiating the Signal receiver hole by strong light

- 2. avoid irradiating the Signal receiver hole by strong light
 3. nake sure the surface is clean before sticking
 4. please use it after 24 hours after 3M sticker works
 5. The continuous flashing of led indicator and the intermittent prompting
 sound indicate low power of the holder, which should be charged.
 6. the alarm will last for 4 minutes in a time
 7. before replacing the 3M sticker at the botton of holder, you should use a
 blower heating the area around where the holder botton and desktop were
 adhered, thus weakening the adsorption property and easier to separate.
 8. Reactivation is needed when LED indicator was lost or should be replaced
 for some reasons
 9. you can reactivate the holder in the following two situations:
 (1) Repeat the types as above
 (2) Most is glosed to the table, not easy to umplug, you can let the host in alarm, detection
 state, the bost of the code, for example; you can unglay the crystal in the crystal of
 the host side of the jack head, so that the host in a non-alarm status.

Contact way:

D.F.S Technology (HK) Co., Limited
D.F.S Metal Goods Co., Ltd
D.F.S Metal Goods Co., Ltd
TEL: +86-752-990174 / 27058017/27689276
FEB. +86-752-990174 / 27058017/27689276
FEB. +86-752-990174 / 27058017/27689276
FEB. +1005 / 2705